HS-100RT Accelerometer

AC acceleration and PT100 temperature output via PUR Cable

Key Features

- Temperature output PT100
- Waterproof
- Resistant to oil

Industries

Building services, Pulp and Paper, Mining, Metals, Utilities, Automotive, Water, Pharmaceutical





Technical Performance

Mounted Base Resonance	see 'How To Order' table (nominal)
Sensitivity	see: 'How To Order' table ±10%
	Nominal 80Hz at 22°C
Frequency Response	2Hz (120cpm) to 10kHz (600kcpm) ± 5%
	1.5Hz (90cpm) to 12kHz (720kcpm) ± 10%
	0.8Hz (48cpm) to 15kHz (900kcpm) ± 3dB
Isolation	Base isolated
Range	see: 'How To Order' table
Temperature Output	PT100 (100 Ohms)
Transverse Sensitivity	Less than 5%

Mechanical

Case Material	Stainless Steel
Sensing Element/Construction	PZT/Compression
Mounting Torque	8Nm
Weight	106gms (nominal) body only
Maximum Cable Length	1000 metres
Standard Cable Length	5 metres
Screened Cable	PUR - length to be specified with order
Mounting Threads	see: 'How To Order' table
Submersible Depth	100 metres max (10 bar)

Electrical

Excitation Voltage	18-30 Volts DC
Electrical Noise	0.1mg max
Current Range	0.5mA to 8mA
Bias Voltage	10 - 12 Volts DC
Settling Time	2 seconds
Output Impedance	200 Ohms max.
Case Isolation	$>10^8$ Ohms at 500 Volts

Environmental

Operating Temperature Range	-30 to 90°C
Sealing	IP68
Maximum Shock	5000g
EMC	EN61326-1:2013

Typical Frequency Response (at 100mV/g)



Applications

Fans, Motors, Pumps, Compressors, Centrifuges, Conveyors, Air Handlers, Gearboxes, Rolls, Dryers, Presses, Cooling, VAC, Spindles, Machine Tooling, Process Equipment

Vibration sensor should be firmly fixed to a flat surface (spot face surface may be needed to be produced and cable anchored to sensor body.)



How To Order

Product Prefix
HS - Hansford Sensors

Product Series
100 - Industrial Vibration Sensor

Cable Length
QXX - length specified in metres

H	S	1	0	0	R	T	X	X	X	X	X	X	X	X	X	X

Extra Options (if required)
F - Filtered
I - Intrinsically Safe
L - 316L Stainless Steel
RT - Temperature Output PT100
S - 90° Side Exit
Y - 5% tolerance on sensitivity

Sensitivity	Range	Resonant Frequency
010 - 10mV/g	±800g	34kHz (2,040kcpm)
030 - 30mV/g	±250g	33kHz (1,980kcpm)
050 - 50mV/g	±160g	32kHz (1,920kcpm)
100 - 100mV/g	±80g	30kHz (1,800kcpm)
250 - 250mV/g	±32g	28kHz (1,680kcpm)
500 - 500mV/g	±16g	26kHz (1,560kcpm)

Cable/Connector
01 - PUR
54 - M12

Mounting Threads
01 - ¼-28" UNF Female
02 - ¼-28" UNF Male
05 - Quick Fit Female
06 - M6 x 1mm Male
08 - M8 x 1.25mm Male
10 - M10 x 1.5mm Male

Hansford Sensors
Excellence in Vibration Monitoring

www.hansfordsensors.com
sales@hansfordsensors.com

We reserve the right to alter the specification of this product without prior notice

TS291.8